



The Angle Andy 25 profile is perfect for mounting in corners of joinery, corners of perpendicular walls or into the corner of a wall and ceiling. Angle Andy 25 features one smooth side, meaning it is not confined to corner mounting, but can also be mounted with one side of the extrusion visible - ideal for wall washing or glass cabinetry.

MOUNTING OPTIONS		DIFFUSER OPTIONS		SUPER SERIES LED STRIP OPTIONS		
Surface mounted		Opal		Lumens per metre	Watts per metre	Colour temp.
Rod suspended		Clear		310lm		2700K
				330lm	3W	3000K
				345lm		4000K
				760lm		2700K
				800lm	7W	3000K
				840lm		4000K
				1520lm		2700K
				1600lm	14W	3000K
				1680lm		4000K
				1955lm		2700K
				2060lm	20W	3000K
				2160lm		4000K

- LED strip options vary depending on region – please consult your local distributor for more information. Other LED strip options are available on request, including IP54 and IP67.  
- All lumen values refer to the bare LED strip. Losses through diffuser/profile are not represented. Consult photometric data.  
- 5 year manufacturer's warranty on Super Series & Spec Series LED strip.

## ACCESSORIES

JMC-12  
Joinery mounting clip

JN-ST-12  
Straight joiner

JN-90-12  
90 degree joiner

JN-120-12  
120 degree joiner

JN-135-12  
135 degree joiner

SRK-1-S / SRK-1-W / SRK-1-B  
Rod suspension kit (rod not incl)

SRK-6-S / SRK-6-W / SRK-6-B  
Rod suspension kit (rod not incl)

ROD-0.5M / ROD-1M / ROD-2M  
Suspension rod - 0.5m, 1m, 2m

## ADDITIONAL INFORMATION

Applications	Task lighting in kitchen cabinetry, lighting for shelving or display units, hallway lighting, wall-washing.
Installation	Interior or exterior (with IP67 rated LED strip).
Materials	Extruded aluminium body, polycarbonate diffuser, AES plastic end caps.
Finish	Natural silver anodised or custom powder coat.
Light source	LED ribbon strip.
Power supply	24V DC - remote driver options ranging from 6W up to 320W.
Dimmable	Various options available, please enquire.





