



## DADO DAVE 20





Dado Dave 20 is a sleek, architectural profile designed to provide high-output up lighting. The LED strip is positioned to maximise asymmetric distribution which offers smooth light out into the space. The concealed light source keeps glare to a minimum, while up to 2650lm per metre LED strip means it packs a punch. The extrusion is designed for super-quick screw-fixing, while a clip-in aluminium lid covers the screw heads and provides a smooth, easy-to-clean surface. For applications where Dado Dave 20 is being mounted flush with the bottom of a bulkhead, then the mounting adaptor can be used to reverse the direction of the mounting screw.

## MOUNTING OPTIONS

Surface mounted

| DIFFUSER | OPTIONS |
|----------|---------|
|          |         |

Opal Clear Prismatic

| SUPER SERIES LED STRIP OPTIONS |           |                 |   |             |  |  |  |  |
|--------------------------------|-----------|-----------------|---|-------------|--|--|--|--|
| Lumens p                       | oer metre | Watts per metre | С | olour temp. |  |  |  |  |
| 310lm                          |           |                 |   | 2700K       |  |  |  |  |
| 330lm                          |           | 3W              |   | 3000K       |  |  |  |  |
| 345lm                          |           |                 |   | 4000K       |  |  |  |  |
| 760lm                          |           |                 |   | 2700K       |  |  |  |  |
| 800lm                          |           | 7W              |   | 3000K       |  |  |  |  |
| 840lm                          |           |                 |   | 4000K       |  |  |  |  |
| 1520lm                         |           |                 |   | 2700K       |  |  |  |  |
| 1600lm                         |           | 14W             |   | 3000K       |  |  |  |  |
| 1680lm                         |           |                 |   | 4000K       |  |  |  |  |

| Lumens per metre |     | Watts per metre |       | Colour temp. |  |
|------------------|-----|-----------------|-------|--------------|--|
| 1955lm           |     |                 | 2700K |              |  |
| 2060lm           |     | 20W             |       | 3000K        |  |
| 2160lm           |     |                 |       | 4000K        |  |
| 2400lm           |     |                 |       | 2700K        |  |
| 2530lm           | 26W |                 | 3000K |              |  |
| 2650lm           | •   |                 |       | 4000K        |  |
|                  |     |                 |       |              |  |

- LED strip options vary depending on region - please consult your local distributor for more information. Other LED strip options are available on request, including RGB & RGBW.

- All lumen values refer to the bare LED strip. Losses through diffuser/profile are not represented. Consult photometric data.
- 5 year manufacturer's warranty on Super Series & Spec Series LED strip.

## ACCESSORIES







JN-90-22



MA-4M Bulkhead mounting adaptor

## ADDITIONAL INFORMATION

**Applications** Concealed indirect lighting for living rooms, board rooms, hallways.

Installation Interior only.

Extruded aluminium body, polycarbonate diffuser, aluminium end caps. Materials


Finish Natural silver anodised or custom powder coat.

Light source LED ribbon strip.

24V DC - remote driver options ranging from 6W up to 320W. Power supply

Dimmable Various options available, please enquire.





Polar curve for 1890 lumen LED strip with clear diffuser.



