



DOWNHILL DAN 35





Downhill Dan 35 is a quick-to-install, recessed down-lighter profile. The asymmetric mounting bracket makes this product unique and means that it can be installed with the LED strip already attached. Downhill Dan 35 has plenty of power for a huge range of applications. Silver anodised or white powder coat are standard finish options.

	\cap	пп	NIII.	II NI		\circ	PITE	\circ	NS	
W	U	U.	NЦ	ШК	U	U	ш	U	CVI	

Recessed

DIFFUSER OPTIONS Satin

Black

L
3
3

SUPER S	ERIES LED S	TRIP OPTIONS	
Lumens	per metre	Watts per metre	Colour temp.
310lm			2700K
330lm		3W	3000K
345lm			4000K
760lm			2700K
800lm		7W	3000K
840lm			4000K
1520lm			2700K
1600lm		14W	3000K
1680lm			4000K

Lumens per metre	Watts per metre	Colour temp.	
1955lm		2700K	
2060lm	20W	3000K	
2160lm		4000K	
2400lm		2700K	
2530lm	26W	3000K	
2650lm		4000K	

- LED strip options vary depending on region - please consult your local distributor for more information. Other LED strip options are available on request, including IP54 and IP67.

- All lumen values refer to the bare LED strip. Losses through diffuser/profile are not represented. Consult photometric data.
- 5 year manufacturer's warranty on Super Series & Spec Series LED strip.




JN-ST-23



JN-90-23



MB-DD35



SMRB Seismic restraint bracket

ADDITIONAL INFORMATION

Applications General downlighting in kitchens, living rooms, dining rooms, reception counters, lobbies.

Interior or exterior (with IP65/IP67 rated LED strip). Installation Materials


Extruded aluminium body, polycarbonate diffuser, aluminium end caps. Natural silver anodised, textured white powder coat or custom powder coat colours. Finish

Light source LED ribbon strip.

24V DC - remote driver options ranging from 6W up to 320W. Power supply

Dimmable Various options available, please enquire.





Polar curve for 2250 lumen LED strip with satin

