



# Richie Rail 17





Richie Rail 17 is a unique illuminated handrail system. CNC machined wall brackets provide a beautiful finish and make for quick installation. Hollow wall brackets conceal the power supply to the LED strip, and the low voltage input makes the handrail safe to touch. Richie Rail 17 is suitable for use on residential and commercial stairs and thoroughfares.

# MOUNTING OPTIONS

### Wall mounted

# DIFFUSER OPTIONS

Clear

Lumens per metre		Watts per metre		Colour temp.	
310lm				2700K	
330lm		3W		3000K	
345lm				4000K	
760lm				2700K	
800lm		7W		3000K	
840lm				4000K	
1520lm				2700K	
1600lm		14W		3000K	
1680lm	•			4000K	

- LED strip options vary depending on region – please consult your local distributor for more information. Other LED strip options are available on request, including IP54 and IP67.

- All Limen values refer to the bare LED strip. Losses through diffuser/profile are not represented. Consult photometric data.

- 5 year manufacturer's warranty on Super Series & Spec Series LED strip.



WBRR17-H-MSA-S



WBRR17-H-MSA-R Wall bracket with round cover



JN-ST-RR17



WBPBS-10 Wall bracket plasterboard spacer, 10mm



WBPBS-13 Wall bracket plasterboard spacer, 13mr



JN-90-RR17 90 degree bend



JN-V-RR17



WBRR17-H-MSA-S Glass mount bracket with square cover



WBRR17-H-MSA-R Glass mount bracket with round cover

## ADDITIONAL INFORMATION

Residential or commercial stairs, lift cars, accessways. **Applications** Installation Interior or exterior (with IP67 rated LED strip).

Materials Extruded aluminium body and components, polycarbonate diffuser.


Finish Natural silver anodised or custom powder coat colours.

Light source LED ribbon strip.

24V DC - remote driver options ranging from 6W up to 320W. Power supply

Dimmable Various options available, please enquire.





Polar curve for 1890 lumen LED strip with opal

